FS-9120DN

▶ print ▶ copy ▶ scan ▶ fax

THE VERSATILE A3 DEPARTMENTAL PRINTER



- 36 pages per minute in A4 with 1,200 dpi quality 20 pages per minute in A3 with 1,200 dpi quality
- Automatic duplex and network-ready as standard
- 1,200 sheets input as standard, upgradeable to 4,200 sheets
- 8 emulations including PCL6, PS 3 and PDF direct printing
- Warm-up time: only 25 seconds from power on
- Lowest cost per page in its class

The FS-9120DN from Kyocera is an outstanding combination of speed and impressive paper handling built for your department needs. It comes with duplex and network functionality as standard and delivers up to 36 A4 pages per minute. In standard configuration, the FS-9120DN handles three different paper sizes or media types with a total volume of 1,200 sheets. For growing demands the FS-9120DN offers impressive paper handling upgrade options for up to 4,200 sheets input capacity as well as the choice between three powerful finishers. The high performance of the PowerPC 750CX / 400 MHz CPU enables best use of the engine. Lowest cost per page in its class and cost savings from the beginning result in an unbeatably low TCO. Experience the flexible FS-9120DN.





FS-9120DN

Monochrome A3 **Departmental Printer**

The ECOSYS technology is based on extremely durable components. The drum, developer and fuser of the FS-9120DN are designed for 500,000 pages. As toner is the only consumable required, ECOLaser printers operate with the lowest cost per page in their class, and they are particularly environmentally friendly. Thanks to their modular system and flexible paper options all ECOLaser printers can be configurated to meet your exact requirements.

The FS-9120DN delivers outstanding network connectivity and problem-free system administration. Kyocera's single platform technology means that the same driver can be used for every Kyocera PCL/PostScript print device in the network: from single-user desktop printers to high-end multifunctional systems. Only Kyocera offers this effortless combination of IT sophistication and high-performance paper handling expertise. Duplex and network functionality is standard in the FS-9120DN.

Technology: Kyocera ECOSYS, Laser

Engine speed: Max. 36 pages per minute A4, max. 20 pages per minute A3

Resolution: 1,200 dpi quality (1,800 x 600)

Time to first page: 7 seconds Warm-up time: 25 seconds from power on

Duty cycle: Max. 180,000 pages per month, average 55,000 pages pages per month

Power source: AC 220 ~ 240 V. 50/60 Hz

Power consumption: Printing: 920 W, Stand-by: 160 W,

Power-Saving (ECOpower): 12 W Noise (ISO 7779): Printing: 53 dB(A), Stand-by: 39 dB(A),

Power-Saving (ECOpower): Immeasurably low Dimensions (W x D x H): 585 x 639 x 615 mm

Weight: Main unit: Approx. 67 kg Certifications: TÜV/GS, CE, PTS

This product is manufactured according to ISO 9001 guality standard and ISO 14001 environmental standard.

All mentioned paper quoted are based on a paper thickness of max, 0.11 mm. Please use paper recommended by Kyocera under normal environmental condition.

Input capacity: 2 x 500-sheet universal paper cassette 60-105 g/m², A3, A4, A4-R, A5, B4, B5, B5-R, Letter, Letter-R, Legal, Ledger, Folio, STMT

200-sheet multi-purpose tray, 60-200 g/m², A3-A6R, Custom (88 x 148 mm to 297 x 450 mm)

Max. input capacity with optional paper feeder PF-75: 4,200 sheets Duplex as standard

Output capacity: 500 sheets face-down

CONTROLLER

Processor: PowerPC 750CX / 400 MHz Memory: Standard 32 MB + ECOmemory, max. 544 MB (2 DIMM slots)

Emulations: PCL6/PCL5e incl. PJL, KPDL 3 (PostScript 3 compatible), PDF direct print, automatic emulation sensing (AES), KC-GL (HP-7550A), Line Printer, IBM Proprinter X24E, Epson LQ-850, Diablo 630

Controller language: PRESCRIBE IIe

Fonts: 80 outline fonts (PCL), 136 PostScript Fonts, 1 bitmap font, 45 types of one-dimensional barcodes plus two-dimensional barcode PDF-417

Downloadable fonts: Kyocera, PCL + TrueType format, Type 1 + 3 format

Print features: eMPS – job management functionality with optional hard disk HD-4 for quick copy, proof and hold, private print and job storage

Your Kyocera Business Partner:

With the Kyocera page design and control language PRESCRIBE IIe, even complex graphics, logos and forms (even multipart forms) can be created independently of the system and saved and updated in the printer. Consequently, integration into print files no longer applies. They are only accessed as required and therefore relieve the load on the network.

The 136 scalable high quality PostScript fonts provide high flexibility for all applications. A total of 45 integrated barcodes including hash totals are computed automatically by the printer and printed in the desired size, alignment and position.

Standard interface: Fast Ethernet 10/100Base-TX, High speed bi-directional parallel (IEEE 1284), USB 2.0 (Hi-Speed), KIJIO-IV option interface slot

Multiple interface connection (MIC): Allows simultaneous data transfer via up to four interfaces, with each interface having its own virtual printer.

Paper handling PF-70 Paper feeder: 2 x 500 sheets, 60-105 g/m², A3, A4 A4-R, A5, B4, B5, B5-R, Letter, Letter-R, Legal, Ledger, Folio, STMT

PF-75 Paper feeder: Max. 3,000 sheets, 60-105g/m², A4, **B5** Lette

DF-71E Document finisher + AK-71P: 250 sheets face-up, max, 3.000 sheets A4 or 1.500 sheets A3 face-down, max 50 sheets A4 or 30 sheets A3 stapling at 3 positions, 2 or 4 hole punch

M-2107 Mailbox: 7 bins x 100 sheets mailbox, A3-A5R, for DF-71E

DF-73 Document finisher: Max. 1,000 sheets, one position stapling max, 30 sheets

DF-75R Document finisher + RA-1 + AK-71P: Max. 1,000 sheets A4 or 500 sheets A3, staple max. 50 sheets A4 or 30 sheets A3, stapling at 3 positions, Booklet folding

and stapling max. 40 pages (10 sheets) PH-2B/PH-2C/PH-2D Punch unit for DF-75R: 2-hole/4-hole/ Swedish type

CB-70 Cabinet (W x D x H): 590 x 600 x 320 mm desk with storage capacity

Memory

Printer memory: 2 slots (16, 32, 64, 128 or 256 MB DIMM) CompactFlash® card: 1 slot (8, 16, 32, 64 MB), forms, fonts, logos, macro storage HD-4 Hard disk: 20 GB, storage of data, forms, fonts and job

management

Optional interface

IB-21E Network card: 10Base-T/100Base-TX

SB-50 Network card: 10Base-FL, FibreLink

SB-60 Network card: TokenRing STP/UTP

SB-70 Network card: Wireless LAN - IEEE 802.11b SB-110FX Network card: 10Base-T/100Base-TX/100Base-FX.

FibreOptic SB-140 Network card: 10Base-2/10-Base-T/100Base-TX SB-80 Parallel interface: 2nd parallel interface – IEEE 1284 IB-11 Serial interface: RS-232C serial interface

KM-NET Viewer is an advanced network management software tool that is compatible with all Kyocera printers and multifunctional products as well as those of other vendors by using the standardized protocol SNMP. The settings of all printers on the network can be checked visually and amended from any Windows PC. KM-NET Viewer also acts as a valuable, real-time early warning system by sending eMail-Messages.

The CompactFlash[®] card offers abundant storage space for typefaces, logos, standard forms and signatures as well as individual API or PRESCRIBE macros.

The optional hard disk offers even more efficient document management. At the same time it enables the management of print data with eMPS functions such as quick copy, proof and hold, private print and job storage.

TK-70 Toner-kit: Microfine toner for 40,000 pages with 5 % coverage (ISO 10561B) 70,000 pages according to Dr. Grauert letter (ISO 10561A)

Capacity of starter toner is 20,000 pages with 5 % coverage (ISO 10561B)

2-year warranty as standard. Kyocera guarantees the drum and developer for 3-year or 500,000 pages (whichever occurs sooner), provided each printer is used and cleaned in accordance with the service instructions.



The up to 5-year on-site warranty extension for printer and options. The warranty is limited to 2 million pages (3 million pages with KYOlife)

FS-9120DN/E: FS-9120DN + PF-70 + AK-71P + DF-73 FS-9120DN/B: FS-9120DN + PF-70 + AK-71P + DF-75 + RA-1 FS-9120DN/D: FS-9120DN + PF-75 + AK-71P + DF-71E + M-2107



Ecosys

Select your options to suit your needs:

Document finisher (DF-75R)



Kyocera Mita Europe B.V., Hoeksteen 40, 2132 MS Hoofddorp, The Netherlands, Tel +31 (0) 20 65 40 000, Fax +31 (0) 20 65 31 256, www.kyoceramita-europe.com, info@kyoceramita-europe.com

Kyocera Mita Corporation, 2-28, 1-Chome, Tamatsukuri, Chuo-Ku, Osaka 540-8585, Japan, www.kyoceramita.com

Kyocera does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

KYOCERa

- Paper feeder (PF-75)

(max. 115.2 kbps)